





PRODUCT DETAILS



Dimensions



Accessories



CLASSIC ASYM

CLASSIC ASYM POLISHED ASYM REF FDH
G5 1x28W, ECG, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling surfaced / suspended (SSx)
LIGHT SOURCE	Linear fluorescent lamp T5 (FDH)
OPTICAL SYSTEM	Asymmetric polished reflector (ASP)
LIGHT DISTRIBUTION	Asymmetric
WIRING	Electronic control gear FIX (ECG) On request: Electronic control gear DALI (EDA) Emergency unit variant (1H / 3H)
MATERIALS	Housing: sheet steel Reflector: polished aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Rope suspension
VOLTAGE	220-240 V, 50-60 Hz
NUMBER OF LAMPS	1
POWER	1 x 28 W
LAMPHOLDER	G5
EEC	A+ / A / B
PROTECTION CLASS	I
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1235 x 180 x 85 mm
WEIGHT	3,9 kg

AREAS OF APPLICATION [ARCHITECTURE AND MEDIA](#)


[EDUCATION](#)

[RETAIL AND PRESENTATION](#)





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.