




PRODUCT DETAILS



Dimensions



Accessories



EDAN RECESSED

EDAN RECESSED S RCD MATT ASYM REF
LED 2300lm/830 1x24W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Ceiling recessed RCD - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Asymmetric matt reflector (ASM)
LIGHT DISTRIBUTION	Asymmetric
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Housing: sheet steel Reflector: matt anodised aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2300 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	24 W
SYSTEM EFFICACY	96 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	595 x 123 x 83 mm
WEIGHT	2 kg

AREAS OF APPLICATION

- ARCHITECTURE AND MEDIA
- EDUCATION
- RETAIL AND PRESENTATION

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.