


Optiwall 6

3099-K68

Optiwall Stainless Steel



143x42

Wall Recessed guidance luminaire with Led

- Steplight designed in small dimensions.
- Powered by SMD LED with convex glass optic.
- LED source 6800K CRI>80 of xx nominal lumen.
- System power 1W; System efficacy xxlm/W; xx delivered lumen.
- Control gear housing and light head made of die cast in superpure aluminium.
- 600mm rubber cable and formwork are included.
- 220-240V 50/60Hz integral control gear is inclusive.
- Available in version Square and Round.

Accessories

(To be ordered separately)

Item	Code
IP68 Fast Connector M20	2577
IP68 Junction Box	2355

Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
--------------	--------	-------------------	-----	------------	--------------	------

3099	84 - Stainless Steel	K68-6800K	>80			
------	----------------------	------------------	-----	--	--	--

Ordering code example : 3099 - __ K68 __

Europe - Milano - tel. (+39) 02 9354 0300
formaitalia@formalighting.it

Asia - Hong Kong - tel. (+852) 2516 6500
forma@forma.com.hk

USA
forma@formalightingusa.com

We reserve the right to change specifications without prior notification.

www.formalighting.com